

OZONE GENERATOR

COM-AD-02



FEATURES

- METAL FREE
- WELDED, NO SEALS
- MAINTENANCE FREE
- NO EMISSION OF PARTICLES
- WEAR OUT FREE
- NO CAPACITY WORSENING

APPLICATION

- SEMICONDUCTOR PROCESSING
- FOOD PROCESSING
- WATER STERILIZATION
- RESEARCH & DEVELOPMENT
- ULTRA PURE WATER TREATMENT
- PHARMAZEUTICAL PRODUCTION
- PILOTS WASTE WATER TREATMENT




SPECIFICATIONS

- POWER SUPPLY:
230 V, 50/60 HZ, 0,6 A
115 V, 50/60 Hz (OPTION)
- OZONE GENERATION:
8gO₃/h @ 250NI/h
- OZONE CONCENTRATION:
UP TO 150 gO₃/Nm³
- FREQUENCY CONTROLLED
- LINEAR PRODUCTION RANGE
- REMOTE CONTROL (OPTION)
- CONTROL RANGE: 0-100%
- AIR COOLED


ENCLOSURE

- 19" INSERTION:
3 HU (133mm), DEPTH 365MM
WEIGHT: 9 KG
- TABLE HOUSING:
515(W) X 400(D) X 165(H) MM
WEIGHT: 15 KG

TEST CONDITIONS: FEED GAS: SEP (94% O₃, 6% N₂), ROOM TEMPERATURE: 23°C



DISTRIBUTED BY: _____



MANUFACTURER: _____



ANSEROS

ANSEROS KLAUS NONNENMACHER GMBH

D-72070 TÜBINGEN · DISCHINGERWEG 11
 PHONE +49.7071-7995-0 · FAX +49.7071-7995-95
INFO@ANSEROS.DE · WWW.ANSEROS.DE