


6 motor (oil-lubricated)

Voltage	V	100	100	120	200	200	230	230				
Frequency	Hz	50	60	60	50	60	50	60				
Motor	HP	0.54	0.54	0.54	0.46	0.46	0.46	0.46				
	kW	0.40	0.40	0.40	0.34	0.34	0.34	0.34				
Displacement	l/min	50	60	60	50	60	50	60				
	CFM	1.77	2.12	2.12	1.77	2.12	1.77	2.12				
FAD @ 8 bar	l/min	32	37	37	32	37	32	37				
	CFM	1.13	1.31	1.31	1.13	1.31	1.13	1.31				
Max. pressure ¹⁾	bar	8	8	8	8	8	8	8				
	psi	120	120	120	120	120	120	120				
Max. current	A	6.2	6.2	6.2	2.9	2.9	2.9	2.9				
Tank size	litres	-	-	-	-	-	-	-				
	gallon	-	-	-	-	-	-	-				
Weight	kg	14	14	14	14	14	14	14				
	lbs	31	31	31	31	31	31	31				
Noise level	dB(A)/1m	45	45	45	45	45	45	45				
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes	Yes				
Duty cycle		50%	50%	50%	50%	50%	50%	50%				



Dimensions (l x w x h)
280 x 190 x 240 mm / 11 x 7 4/8 x 9 4/8 inch

¹⁾ Higher pressure available upon request

Technical modifications reserved

JUN-AIR®

E-mail: info@jun-air.dk
Internet: www.jun-air.com

