


6000M-150B vertical (oil-less)

Voltage	V	200	200	230	230	3x200	3x200	3x208	3x400 ²⁾	3x440 ²⁾		
Frequency	Hz	50	60	50	60	50	60	60	50	60		
Motor	HP	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5		
	kW	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3		
Displacement	l/min	528	636	528	636	528	636	636	528	636		
	CFM	18.65	22.46	18.65	22.46	18.65	22.46	22.46	18.65	22.46		
FAD @ 8 bar	l/min	270	330	270	330	270	330	330	270	330		
	CFM	9.53	11.65	9.53	11.65	9.53	11.65	11.65	9.53	11.65		
Max. pressure ¹⁾	bar	8	8	8	8	8	8	8	8	8		
	psi	120	120	120	120	120	120	120	120	120		
Max. current	A	24.6	26.4	24.0	24.9	12.8	12.8	12.8	10.8	10.8		
Tank size	litres	150	150	150	150	150	150	150	150	150		
	gallon	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6		
Weight	kg	221	221	221	221	221	221	221	221	221		
	lbs	487	487	487	487	487	487	487	487	487		
Noise level	dB(A)/1m	58	59	58	59	58	59	59	58	59		
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Duty cycle		100%	100%	100%	100%	100%	100%	100%	100%	100%		

cu.ft./min. Ltr./min.



Dimensions (l x w x h)

1220 x 630 x 675 mm / 48 x 24 6/8 x 26 5/8 inch

¹⁾ Higher pressure available upon request

²⁾ Neutral is required in installation

Technical modifications reserved

JUN-AIR®

E-mail: info@jun-air.dk

Internet: www.jun-air.com

